

R


D

M


W



Shape
Round



Clearance Angle
15°



Tolerance
|| ± 0.05
s ± 0.13



Insert Type
Screw down clamping
chip breaker

Insert designation	Grade	l	s	P/r	D	Direction	Catalog Nr.	Page
RDMW 10T3 MO	LT 30	10	3,97	5		Neutral	M0001550	181

Surfacing Insert Lead angle 90°


Application Guide	Surfacing	Copying	Mold-Milling

Multi purpose Round insert, with flat rake surface, designed for hard materials. Suitable for Roughing to Semi-finishing Copying of 3D surfaces and Face milling operations.

Machining Recommendation Guide - Please see Pg. 8		



Catalog Nr.	Description	D	H	L	Ap	z
M2000683	LT 100 W-W-D20	20	80	180	5	2
M2000684	LT 100 W-W-D25	25	80	180	5	3
M2000685	LT 100 W-W-D32	32	105	212	5	3



Material Group	Group No	Material Examples*	Brinell hardness	d.o.c [mm]		feed [mm/tooth]		V _c [m/min]	
				min	max	min	max	min	max
Low Carbon Steel	1	Ck15, Ck45 1020, 1045	150	0.5	3	0.23	0.58	190	350
			180		2.5		0.52		300
			210		1.5		0.45		260
Alloy Steel	2	42 CrMo 4 St 50-2 Ck60 1060 4140	180	0.5	3	0.21	0.52	150	240
			230		2.5		0.47		210
			280	0.5	2	0.2	0.43	130	190
			320		1.5		0.4		170
High Alloy Steel	3	X40 CrMoV 5 1 H 13 40 NiCrMo 6 4340 S 2-10-1-8 HSS M42	220	0.5	2	0.2	0.47	90	150
			280		2		0.43		130
			320	0.5	1.5	0.2	0.4	60	110
			350		1.5		0.38		90
			400	0.3	1	0.2	0.36	40	80
			480		0.5		0.35		70
			550		0.5		0.3		60
Austenitic Stainless Steel	4	X5 CrNi 18 9 304	210 to 250	RDMW inserts are not recommended for Stainless Steel					
	5	X2 CrNiMo 17 2 2 316	230 to 270						
	6	X6 CrNiMoTi 17 12 2 316 Ti Duplex / Nitronic	-----						
Ferritic Stainless Steel	7	X8 Cr 7 430	Annealed						
Martensitic Stainless Steel	8	X15 Cr 13 410	Annealed Treated						
Grey Cast Iron	9	GG 20	140 to 230	0.5	3	0.18	0.6	170	300
		GG 25							250
		GG 30							210
Nodular Cast Iron	10	GGG 40	210	0.5	2.5	0.18	0.5	120	210
		GGG 50	260						170
		GGG 70	310						150
		G-X260NiCr42	450	0.2	0.5	0.12	0.32	30	60
Nickel Based Alloys	11	Inconel 625	-----	RDMW inserts are not recommended for Exotic materials					
		Inconel 718							
		Hastelloy C							
Titanium Based Alloys	12	TiAl 6 V4	-----						
		T40	-----						

RDMW

